



100kWh DC Energy Storage System

- High security
- Stable operation
- Intelligent temperature control
- Automatic fire fighting system



MODULE INTRODUCTION

PERFORMANCE SPECIFICATIONS	
Model	HZEB-HCT-100
Cell type	LiFePO4
Nominal Energy	100.35kWh
Nominal Capacity	280Ah
Nominal Voltage	358.4V
Operating Voltage Range	313.6~403.2V
Combination Method	1P112S
Charge and Discharge Current	140A
Discharge Depth	Max100% (Suggestion80%)
System Protection Rating	IP54
Installation Environment	Out Door
Cooling Method	Air Cooling
Operating Temperature	-10°C~55°C (> 45°C derating)
Operating Humidity	5%~90%RH (non-condensing)
Operating Altitude	< 2000m
Cycled Capacity	6000Cycles
Dimension	1295*1335*2085mm
Weight	1280kg
Module Parameters	
Cell Type	LiFePO4
Nominal Energy	14.336kWh
Nominal Capacity	280ah
Nominal Voltage	51.2V
Recommended Current	140A
Maximum Current	140A
Cooling Method	Fans Cooling
Charging Temperature Range	0°C~55°C
Discharging Temperature Range	-10°C~55°C
Module Protection Rating	IP54

Text and images correspond to the current state of technology at the time of printing, subject to modifications. All information is without guarantee in spite of careful editing—liability excluded



- High-security technology ensures stable and excellent performance
- Compatible with multiple inverters including Sungrow DEYE Solis Growatt Voltronic
- It provides highly efficient energy solutions for household scenarios and small commercial scenarios