



Floor-mounted energy storage system

Data Sheet Residential BESS

Compatibility

Tier 1 Inverter Compatibility

Safety

Multi-protection from self developed BMS

Easy to Scale Up

Be workable to be parallel based on 48V

Efficient Power Cost

Long cycle life and superior performance



HZEB-LCT-20

PERFORMANCE SPECIFICATIONS	
Model	HZEB-LCT-20
Nominal Voltage	51.2V
Sell model/Configuration	3.2V 205Ah /16S2P
Capacity(Ah)	410Ah
Rated Energy(kWh)	20.992kWh
Max.Charge/Discharge Current(A)	150A/150A
Voltage Range(Vdc)	44.8~57.6V
Scalability	Up to 6 parallel
Communication	RS232-PC,RS485(B)-BAT RS485(A)-Inverter,Canbus-Inverter
Cycle Life	≥8000Cycles@25°C, 80%DOD
Warranty Life	10 Years (Cycle Life≥15Years(25°C))
MECHANICAL SPECIFICATIONS	
Weight(Net/Gross)(KG)	180kg
Dimension(W/D/H)(mm)	265*650*973mm
Installation Mode	On the ground
IP Grade	IP21
SECURITY AND CERTIFICATION	
Safety(Pack)	UN38.3,MSDS,IEC62619(CB),CE-EMC
Safety(Cell)	UN38.3,MSDS,IEC62619,CE,UL1973,UL9540
Protection	BMS,Breaker
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature(°C)	Charge 0°C~50°C; Discharge -10°C~50°C
Altitude(m)	≤2000m
Humidity	≤95% (Non-condensing)



Text and images correspond to the current state of technology at the time of printing, subject to modifications.All information is without guarantee in spite of careful editing-liability excluded



- High-security technology ensures stable and excellent performance
- Compatible with multiple inverters including Sungrow DEYE GOODWE Solis Growatt Voltronic
- It provides highly efficient energy solutions for household scenarios and small commercial scenarios